

Blister machine UPS 5

The consistent further development of Uhlmann's most successful and versatile blister machine to date.

Continuing the evolution

The Blister machine UPS 5 is a high-speed machine with a maximum output of 400 blisters/minute. The evolutionary development of this machine model commenced in 1977 with the UPS 1. A total of 900 machines of the four models preceding the UPS 5 – alone 420 of its immediate predecessor the UPS 4 – are in operation throughout the world. At every development stage, our engineers supplemented established technology with innovative components and state-of-the-art engineering to create a new category of machine. Accordingly, the UPS 5 combines the advantages of Uhlmann's most successful and versatile machine to date, the UPS 4, with many new features. The UPS 5 guar-

antees the option of modular extensions, is suitable for the packaging of solids and liquids, allows various modes of operation and, not least, simplifies operation, cleaning and maintenance. And: tools from the UPS 4 can be used on the UPS 5 – we guarantee that.


The UPS 5 is characterized by its large format area and large forming depth. As a result, it is favored for the packaging of liquid products or dispensers, tropical blisters and all-aluminum blisters. It is also used for the packaging of solids and can process plastic as well as all-aluminum blisters with the same consistent precision.



Blister machine UPS 5

The Blister machine UPS 5 at a glance. Technical data:

Output [1/min]	max. 400 blisters	Processable forming materials	Al, PVC, PVC/PVDC, PVC/Aclar, PS, PET
Sealing principle	intermittent		
Format area		Processable lid materials	Al, paper/Al
Index x width	272 mm x 284 mm	Space required	
Forming depth	max. 40 mm	Machine width	approx. 1,950 mm
Reel diameter		Machine height	approx. 1,998 mm
Lid material	max. 460 mm	Machine length	approx. 4,000 mm modular extension possible
Forming material	max. 800 mm		
		Net weight	approx. 4,000 kg



Blister machine UPS 5

Components and features of the UPS 5

- Modular machine frame for variable extension
- Enclosed stations that can be installed separately
- Servo-driven indexes and blister transfer – time-saving as no manual adjustments necessary
- Redesigned heating station, e. g. heating plates with new coating
- Universal forming station for all types of materials, forming depth up to 40 mm
- Integration of different feeding systems for solid and liquid products or medicinal utensils
- Use of UPS 4 tools guaranteed

Additional advantages of the UPS 5

- Fast format changeover as few format parts – no tools are required
- GMP-compliant machine design for straightforward cleaning and maximum pharmaceutical safety
- Central touch screen operation with 3-D visualization
- Innovative door sliding and closing mechanism for optimum accessibility and reduced noise level
- Integration of separate production data acquisition system possible
- Predestined for line integration with the central line control system SCADA

SyPro feeder



Sealing station



Punching station



Germany
Phone +49 (0)7392 702-0
info@uhlmann.de

USA
Phone +1 973 4028855
info@uhlmann-usa.com

Switzerland
Phone +41 (0)61 7022370
info@uhlmann-hoefliger.ch

Great Britain
Phone +44 (0)1252 743-120
info@uhlmann.co.uk

Spain
Phone +34 918 060960
info@uhlmann.es

Sweden
Phone +46 (0)31 450505
info@uhlmann-nordiska.se

Brazil
Phone +55 11 4012 4375
info@uhlmann.com.br

Russia
Phone +7 (495)933 7747
info@pharmaunion.ru

Singapore
Phone +65 673 43150
info@uhlmann-singapore.com

China
Phone +86 21 3302 8658
info@uhlmann.cn

www.uhlmann.de